

Save energy and eliminate waste  
Greatly reduce your gas cost!



Xinersheng Machinery (Jiangsu) Co.,Ltd  
Shanghai Xinran Compressor Co.,Ltd

销售/研发中心: 上海市嘉定区芳林路699弄198栋  
Sales/R&D Center: Building 198, Lane 699, Fanglin Road,  
Jiading District, Shanghai  
电话(Tel): 021-33581065 33580961  
微信(Wechat): 18621809999 13621769700  
邮箱(E-mail): 57179620@qq.com  
网址(Website): www.xinrancompressor.cn  
工厂地址: 中国江苏省徐州市丰县高新区1号  
Manufactory: No.1 High-Tech, Development zone,  
Fengxian, Xuzhou city, Jiangsu province, China  
电话(Tel): 0516-68896955 68896966 68898880  
68896818 68896959 68898882

24 Hours Hotline: 400-110-9566

Please contact our agency about the product  
details, which are as follows  
有关产品详情, 请联系下列经销商



Mine blasting



Well/Geothermal



Field application



Offshore application



Foundation construction



柴油移动空压机  
Diesel mobile air compressor



Shanghai Xinran Compressor Co.,Ltd  
Xinersheng Machinery (Jiangsu) Co.,Ltd





## 选择信然，选择无忧…… Select Xin ran Select Assured……

上海信然压缩机有限公司隶属于亚太通用机械股份有限公司 (ASIA-PACIFIC UNIVERSAL MACHINERY SHARE LIMITED) 旗下，亚太通用机械股份公司简称APU，是引领全球航空工业高科技及工业机械产品生产制造的高科技技术集团公司。信然压缩机是全球较大的空压机生产厂家之一，信然螺杆式空压机拥有多项专利 (证书号：3014875.3014896.3015801.3015468.3015713.3014738.2500520等) 专业从事空压机设计、研发、生产。自1985年开始，作为该领域的开拓者和领军者，信然公司已为当时空压机的设计和生产制订了极高的水准，同时，信然空压机已被公认为高质量压缩空气污染物清除设备，其产品包括：中高压活塞式空压机、固定螺杆式空压机、移动螺杆式空压机、螺杆活塞复合式空压机、无油螺杆空压机、防爆空压机、离心式压缩机、潜孔钻机、空气干燥机、精密过滤器、储气罐、气动工具等，被广泛应用于各个领域。经过ISO9001认证的生产设施和最先进的生产技术，使信然公司成为全球能提供多机组全系列的压缩机生产公司。

信尔胜机械 (江苏) 有限公司由上海信然压缩机有限公司、中国能源工业集团有限公司、亚太通用机械股份公司共同出资，作为上海信然压缩机有限公司江苏生产基地，主要生产上海信然压缩机有限公司全系列产品，同时生产豪华游艇，大型游艇，摩托艇，潜孔钻机，水井钻机。

信然压缩机有限公司自2008年创立以来，历经十多年的风雨，成为中国国内较大的压缩机制造商，同时，也是国际上享有盛名的螺杆式空压机的出口商，年出口量25000台，今天的信然，拥有十多年的空压机专业制造经验，世界先进的自动化加工设备 & 检测设备。

Shanghai Xin Ran Compressor Co., Ltd. is sub-branch of the Asia-Pacific Universal Machinery Co., Ltd. Asia-Pacific Universal Machinery Co., Ltd. Referred to APU, is a leading global aviation industry high-tech and industrial machinery manufacturing high-tech products technology Group Corporation. Xin ran Compressor is the world's manufacturer of air compressors. Xin ran Screw Air Compressor has a number of patents (certificate number: 3014875, 3014896, 3015801, 3015468, 3015713, 3014738, 2500520 etc.) specializing in Air machine design, research and production. Since the beginning of 1985, as the pioneer and leader of compressor industry, XR has designed and manufactured air compressor to develop to a high level, while, Xin ran air compressor has been recognized worldwide as high quality compression air contaminant removal equipment, and its products include: high pressure piston compressor, screw air compressor fixed, mobile screw Air compressor, screw composite piston compressors, oil-free screw air compressor, air compressor explosion, centrifugal compressors, DTH drill car, air dryers, precision, cylinders, pneumatic tools, etc., are widely used in industry. Xin ran passed ISO9001 certification, xin ran company become the world's best supplier which can produce a full range of multi-unit compressor production company. "XIN RAN" world brand, national pride.

Founded by Shanghai Xin ran Compressor Co., Ltd., China Energy Industry Group Co., Ltd., and Asia-Pacific Universal Machinery Co., Ltd. X.E.S. Industrial Co., LTD is the production base of Shanghai Xin ran Compressor Co., Ltd. In Jiangsu Province, the main products are for Shanghai Xin ran compressor Co., Ltd. While the production of luxury yachts, mega yachts, motor boats, DTH drill rig, water well drilling rigs.

Since its founding in 2008, Xin Ran has experienced the vicissitudes of more than 10 years, becomes a bigger compressor manufacturer and a famous screw compressor exporter in the world which equipped with advanced automatic processing and testing equipments. The annual export quantum reaches 25000 sets.

## 技术特点: Technical features



上海信然压缩机有限公司  
Shanghai Xinran Compressor Co., Ltd.



双级喷油螺杆式压缩机，采用玉柴电控柴油机，提供强劲动力，确保高效运行。

Two-stage oil flooded screw air compressor; Yuchai electrically controlled diesel engine; powerful and efficient.

两级干式重载空滤，标配安全滤芯，使您的空压机重度灰尘环境下依然保持高效工作。

Two-stage dry heavy-duty air filter and standard safety filtering element ensure that your air compressor works efficiently in heavy dust conditions.

全天候压缩机油(AWF)，适应任何气候和温度环境(-29-49℃)。

All-weather compressor fluid(AWF) enables the compressor to work in any weather and at any temperature from -29 to 49℃.

豪华LCD多功能控制电脑，精确显示，直观易懂，具有智能控制、保护系统、电子故障记录与诊断等先进功能。

High-end LCD multi-function control computer, with precise display and intuitive reading, provides smart control, protection, electronic failure logging and diagnosis, and other advanced features.



信然移动空压机



信然移动空压机



上海信然压缩机有限公司  
Shanghai Xinran Compressor Co.,Ltd.

Technical Parameters:

Xinran Deep well special diesel fixed screw compressor								
Type	Unit	XR 1010	XR 1017	XR 1029	XR 1030	XR 1035	XR 1040	XR 1050
Pressure	bar	19	23	23/25	31	25	34	40
Capacity	m <sup>3</sup> /min	18	23	29/25	31	35	34	40
Compression Stage		2						
Exhaust valve dimensions		1-G2*,1-G3/4" 1-G2*,1-G3/4" 1-G2*,1-G3/4" 1-G2*,1-G3/4" 1-G2*,1-G3/4" 1-G2*,1-G3/4" 1-G2*,1-G3/4" 1-G2*,1-G3/4"						
Lubricating oil system volume	L	89	75	82	82	87.8	82	100
Fuel tank volume	L	420	600	800	800	876	975	975
Noise level	db(A)	85	85	95	95	100	100	100
Engine brand		Yuchai						
Serial	Model	YC6A260L-20	YC6MK340L-K30	YC6MK400-H300	YC6K500-K30	YC6K550-K30	YC6K550-K30	YC6C1020L
Cylinder number		6						
Output power at rated speed	KW	195	260	295	350	410	429	680
Maximum engine speed (full load)	rpm	1850	1850	1850	1850	1850	1850	1850
Lubricating oil system volume	L	21	23	28	34	58	58	70
Coolant system capacity	L	58	60	52	52	69	52	72
Appearance Size and weight (Standard trailer type)								
Length	mm	3000	3500	3500	4000	4250	4250	6000
Width	mm	1800	1950	1950	2100	2100	2100	2200
Height	mm	2000	2030	2030	2100	2200	2200	2400
Weight	kg	3200	4850	5000	6000	6800	7000	9500

Xinran Electric mobile screw air compressor							
Type	Unit	XR 25	XR 30	XR 50	XR 60	XR 75	XR 100
Pressure	Mpa	0.7/0.8	0.7	0.7/0.8/1.0/1.3	0.7/0.8/1.0/1.3	0.7/0.8/1.0	0.7/0.8/1.0/1.3
Capacity	m <sup>3</sup> /min	3.1/3	3.8	6.6/6.2/5.7/4.6	8/7.7/6.9/6	10.5/9.8/8	13.6/13/11.3/10
Oil content of supply gas	PPM	≤6					
Exhaust valve dimensions		1-G(3/4), 1-G1(1/2)		1-G(3/4), 1-G1(1/2)		1-G(3/4) 1-G1(1/2)	1-G2 1-G1(3/4)
Noise level	db(A)	85	85	90	90	90	90
Output power at rated speed	kw	18.5	22	37	45	55	75
Maximum engine speed (full load)	rpm	2950					
Voltage	V	380					
Starting method		Y-Δ					
Unit drive mode		Direct connection					
Length	mm	2750	2750	3100	3100	3350	3350
Width	mm	1450	1450	1550	1550	1660	1660
Height	mm	1300	1300	1500	2510	1800	2000
Weight	kg	1000	1200	1300	1500	1600	2700



上海信然压缩机有限公司  
Shanghai Xinran Compressor Co.,Ltd.

Technical Parameters:

Xinran Electric mobile screw air compressor							
Type	Unit	XR 120	XR 150	XR 175	XR 200	XR 250	XR 270
Pressure	Mpa	0.8/1.0/1.3	0.7/1.0/1.3	0.7/1.0/1.3	0.8/1.0/1.3	1.7	0.8/1.0
Capacity	m <sup>3</sup> /min	15.4/13.2/11.2	20.8/16.5/13.7	24/23/15.5	26/23.5/19.5	18	33/28
Oil content of supply gas	PPM	≤6					
Exhaust valve dimensions		1-G2, 1-G1(3/4)		1-G2, 1-G1(3/4)		1-G2 1-G1(3/4)	1-G2 1-G1(3/4)
Noise level	db(A)	90	80	100	100	100	100
Output power at rated speed	kw	90	110	132	160	185	200
Maximum engine speed (full load)	rpm	2950					
Voltage	V	380					
Starting method		Y-Δ					
Unit drive mode		Direct Connection					
Length	mm	3350	3550	3550	3900	3950	3870
Width	mm	1660	1750	1750	1850	1850	1850
Height	mm	2000	2100	2100	2200	2200	2250
Weight	kg	2800	3500	3600	4300	4600	5000

Xinran Electric mobile screw air compressor								
Type	单位	XR 150U	XR 175U	XR 270U	XR 330U	XR 270U	XR 470U	XR 330U
Pressure	Mpa	1.7	1.7	1.7	1.7	2	2.5	2
Capacity	m <sup>3</sup> /min	11	13	22	26	21	33	26
Oil content of supply gas	PPM	≤6						
Exhaust valve dimensions		1-G2, 1-G1(3/4)		1-G2, 1-G1(3/4)		1-G2 1-G1(3/4)	1-G2 1-G1(3/4)	1-G2 1-G1(3/4)
Noise level	db(A)	85	90	95	95	100	100	105
Output power at rated speed	kw	110	132	200	250	220	355	250
Maximum engine speed (full load)	rpm	2950						
Voltage	V	380						
Starting method		Y-Δ						
Unit drive mode		Direct Connection						
Length	mm	3800	3950	3950	4200	3950	4700	4200
Width	mm	1750	1750	1850	1950	1820	2100	1950
Height	mm	2115	2240	2200	2350	2200	2850	2350
Weight	kg	3800	4000	5000	6500	5000	7000	6500



Water well industry    Mine blasting    Well/Geothermal    Foundation construction    Offshore Application    Foundation construction





上海信然压缩机有限公司  
Shanghai Xinran Compressor Co., Ltd.

技术参数: Parameters:

Xinran desiel mobile screw compressor							
Type	XR 135-7	XR 185-8	XR 265-8	XR 300-14	XR 400-13	XR 460-14	XR 500-10
Capacity m <sup>3</sup> /min	3.5	5.2	7	8.5	11	13	14
Pressure (Bar)	7	8	8	14	13	14	10
Fuel tank volume (L)	48	85	85	120	210	300	300
压缩级数 Compression stage	单级压缩 single stage	单级压缩 single stage	单级压缩 single stage	单级压缩 single stage	单级压缩 single stage	单级压缩 single stage	单级压缩 single stage
接口尺寸 Interface size	2XG3/4	G3/4, G1 1/4	G3/4, G1 1/4	G1, G1 1/2	G1, G1 1/2	G1, G1 1/2	G1, G1 1/2
发动机型号 Motor no.	4DW91-50GBG3U	4DW91-50GBG3U	YC4D95-H310	YC4A160-H300	YC4A160-H300	YC6J190-H300	YC6J190-H300
制造商 Manufacturer	锡柴 Xichai	锡柴 Xichai	玉柴 Yuchai	玉柴 Yuchai	玉柴 Yuchai	玉柴 Yuchai	玉柴 Yuchai
额定功率 (KW)	33	42	55	97	110	132	132
额定转速 (rpm)	2400	2200	2200	2200	2200	2200	2200
蓄电池电压 (V)	24	24	24	24	24	24	24
整机长度 (mm)	2910	3315	3315	3900	4200	4300	4300
整机宽度 (mm)	1526	1607	1607	1980	1520	1300	1300
整机高度 (mm)	1430	1583	1583	1950	2268	1950	1950
整机重量 (Kg)	950	1200	1350	2000	2300	2500	2500
整机型号 Type							
Type	XR 600-14	XR 750-14	XR 750-20	XR 900-14	XR 1070-24	XR 1170-25	XR 1270-35
排气量 (m <sup>3</sup> /min)	17	21.2	21.2	23.3	30	35	34
额定压力 (Bar)	14	14	20	14	24	25	2.1-3.5
燃油箱容积 (L)	360	380	380	410	480	923	980
压缩级数 Compression stage	单级压缩 Single stage	单级压缩 Single stage	两级压缩 Two stage	单级压缩 Single stage	两级压缩 Two stage	两级压缩 Two stage	两级压缩 Two stage
接口尺寸 Interface size	G1, G1 1/2	G1 1/2, G2	G1 1/2, G2	G1 1/2, G2	G2 1/2, G2	G2, G3/4	G2, G3/4
发动机型号 Motor type	YC6A240-H300	YC6L310-H300	YC6MK340-H300	YC6L310-H300	YC6K500-KT30	YC6K560-KT30	YC6K560-KT30
制造商 Manufacturer	玉柴 Yuchai	玉柴 Yuchai	玉柴 Yuchai	玉柴 Yuchai	玉柴 Yuchai	玉柴 Yuchai	玉柴 Yuchai
额定功率 (KW)	179	239	260	239	348	354-433	429-522
额定转速 (rpm)	1800	1800	1800	2100	1800	1800	1800
蓄电池电压 (V)	24	24	24	24	24	24	24
整机长度 (mm)	5200	5200	5200	5200	5500	3962	5400
整机宽度 (mm)	1960	2060	2060	2060	2300	2200	2200
整机高度 (mm)	2300	2480	2480	2480	2500	2340	2500
整机重量 (Kg)	2800	5600	6200	5800	6800	6800	7500



绿色/改变/生活  
INNOVATION ENERGY  
Innovative technology, environmental life

Partners

信然柴油移动空压机  
Xin Ran Diesel Mobile Air Compressor

